

## CLEAR VINYL TUBIN

### Submittal Information

Part No. 12401-12406  
 Document No. SPEC12401  
 Date 2022-12-05  
 Revision 01

### General Properties

- Material: PVC
- Service Temperature Range: 23 -140 F(±5%)
- Color: Clear

### Specification

Item No.	I.D. (inch)	O.D. (inch)	Wall Thickness (inch)	W.P. PSI	B.P. PSI	Hardness	Length (feet)	U/M	Std. Pkg.
12401	1/4	5/16	0.04	75	300	90	100(±3%)	RL	5
12402	3/8	1/2	0.05	75	300	90	100 (±3%)	RL	5
12403	1/2	5/8	0.05	45	180	90	100 (±3%)	RL	5
12404	5/8	6/8	0.05	45	180	90	100 (±3%)	RL	5
12405	3/4	7/8	0.06	45	180	90	100 (±3%)	RL	3
12406	7/8	1	0.06	45	180	90	50 (±3%)	RL	3

### Features

- Super smooth dense bore maximizes flow and reduces sediment build up.
- Easy to shape, bend and install, can be cut to size as needed.
- Can be used in a wide variety of settings involving chemicals, gases, and liquids.
- Resistant to acids, alkalis, a variety of chemicals, gases, and liquids.
- Great for low-pressure applications because of the high-quality material.

### Applications

- Use for refrigeration and air conditioning condensation drains.
- Use for aquariums, drain hoses, bath and spa jets, dishwasher inlets and more.
- Cannot be used as tubing for drinking water.

