

BRAIDED VINYL TUBING

Submittal Information

Part No. 12407-12411
 Document No. SPEC12407
 Date 2022-12-05
 Revision 01

General Properties

- Material: PVC & Polyester Reinforces Braiding
- Service Temperature Range: 23 -140 F(±5%)
- Color: Clear

Specification

Item No.	I.D (inch)	O.D. (inch)	Wall Thickness (inch)	W.P. PSI	B.P. PSI	Hardness	Length (feet)	U/M	Std. Pkg.
12407	1/4	7/16	0.10	200	800	90	50 (±3%)	RL	5
12408	3/8	9/16	0.10	200	800	90	50 (±3%)	RL	5
12409	1/2	11/16	0.10	150	600	90	50 (±3%)	RL	5
12410	5/8	13/16	0.10	150	600	90	50 (±3%)	RL	5
12411	3/4	1	0.12	150	600	90	50 (±3%)	RL	3

Features

- Braided PVC construction.
- Smooth, dense bore maximizes flow and reduces sediment buildup.
- Light weight and flexible, can be cut to size as needed.
- Resistant to acids, alkalis, a variety of chemicals, gases, and liquids.
- Has four times the working pressure of single wall PVC.

Applications

- Use for refrigeration and air conditioning condensation drains.
- Use for aquariums, drain hoses, bath and spa jets, dishwasher inlets and more.
- Cannot be used as tubing for drinking water.

